

Gulf of Mexico

Infrastructure

- Approximately 22 ADS-B ground stations located on oil platforms and along the shore
- Approximately 35 Weather sensor stations
- 12 existing communication stations
- 7 new communication stations

Service Volumes – (Communications and Surveillance)

- Low Altitude En Route Service Volume
 - -1,500 ft. 3,000 ft. above mean sea level (MSL) over oil/gas platforms
- High Altitude En Route Service Volume
 - Floor: 28,000 ft. MSL, Ceiling: 60,000 ft. MSL

Services

- Air traffic control separation services
 - ADS-B / ADS-R for Low Altitude up to 24,000 ft.
 - ADS-B 1090-ES only for High Altitude above 24,000 ft.
- VHF Voice Communications (Air to Ground)
- Automated Weather Observation Services
- Flight Information Broadcast Services (FIS-B) Product Set 2 Low Altitude
- (future) Traffic Information Broadcast Services (TIS-B) along shore areas as part of Nationwide roll-out after In Service Decision

Interface Protocols

- Common Digitizer-2 as a virtual radar for integration with legacy automation
- ASTERIX Category 33 for position data and Category 23 service status for integration with ERAM releases

Service Delivery Points (SDP)

- Primary SDP: HOST / ERAM automation system at Houston Center
- Other SDPs
 - Surveillance and Broadcast Services monitor receives service status reports and equipment status reports, as well as ADS-B and FIS-B data
 - FAA monitoring takes place at the William J. Hughes Technical Center and the Aeronautical Center
 - Service certification is at the service delivery point for each automation platform

Applications

- · Air traffic control surveillance
- Weather reporting for instrument flight rules flights
- Voice communications (controller / pilot)
- Enhanced visual acquisition
- · Weather and NAS situational awareness

Benefits

- · High altitude
 - Increased capacity
 - Optimal routing
 - Low altitude
 - Increased capacity
 - Reduction in weather related accidents

V2 Nov 08

